



SPECIFICATION

Recessed Soap Dispenser shall hold and dispense 47 oz (1.4 liters) of liquid, lotion or detergent soap from a multi-purpose push valve. Dispenser tank, door, mounting frame and push button valve shall be fabricated of alloy 18-8 stainless steel, type 304. Door and tank shall be fabricated as one integral unit from No18 gauge. Mounting frame shall be fabricated of No 22 gauge. Door shall be held closed with a tumbler lock keyed alike to other ASI Washroom Equipment and have 1/2" (13mm) square return to wall. Cabinet shall have no exposed fastening devices. An impact resistant clear plastic liquid level indicator shall be provided. Valve shall be constructed of a chrome-plated brass body with stainless steel and plastic internal parts. All exposed surfaces shall be No 4 satin finish and be protected during shipment with a PVC film easily removable after installation.

Recessed Soap Dispenser shall be Model No 0326 as supplied by JD MacDonald.

INSTALLATION

Unit is mounted in wall recess using two (2) No10 self tapping screws (supplied by others) through concealed mounting holes provided. For compliance with Australian Standards 1428.1 and 1428.2, unit shall be installed with the height of its operative component or outlet not less than 900mm and not more than 1100mm above the plane of the finished floor. Note that top of RWO is 9/16" (14mm) below top of unit. Rough Wall Opening (RWO) required is 9"W x 4-7/8"H x 4"D (229mm x 124mm x 102mm).

OPERATION

Soap is manually dispensed by pushing valve button until supply is depleted. Unit may be refilled easily by removing door/tank assembly with a partial load in-place and will continue to feed properly. Tank supply is refilled manually on cycle determined by maintenance needs.

