



#### FEATURES

Designed for quiet operation. Automatic operation. Durable stainless steel finish. Tamperproof & safe intake opening. Easy installation. Electrical connection by cord & plug or direct wiring. Applause dryer can be installed with cord & plug over power point (GPO) to create impression of direct wiring. Made in Australia.

#### SPECIFICATION

Electrical 230/240V. Supply 50Hz AC 10 AMP. Motor 65Watt, 2500 RPM. Element 1.6KW protected by thermal cut-out. Air velocity 16.2m/s. Noise level 69dB (A). Gross 5.3kg Shipping 5.9kg. Certificate of Suitability no. CS/761/Q. Electrical Safety Requirement AS 3304-1995.

**Applause Satin Stainless Steel** shall be Model No A APP02/SSS as manufactured by JD MacDonald.

#### FINISH

Satin stainless steel 304, 16 gauge s/steel with no.4 brushed finish. Charcoal trim.

#### RECOMMENDED INSTALLATION HEIGHT

Men's washrooms 1200mm. Women's washrooms 1150mm. Children's washrooms ages 11-15 1110mm. Disabled person's washrooms 1000mm. Children's washrooms ages 5-10 850mm.

#### WARRANTY

JD MacDonald Applause hand dryers are guaranteed against defective materials and faulty workmanship for 12 months from date of purchase, subject to being installed and maintained in accordance with the Installation and Operating Instructions supplied with the dryer.

